

PACH5N Narrow 5 Ton Compact Horizontal

- Temporary Cooling Only
- Cooling & Heating
- 10 kW & 15 kW Electric Heat



Horizontal Cooling / Heating

Designed to fit through a standard 36" door opening, the PACH5N allows for increased tonnage and static pressure in places never thought obtainable with a 5-ton unit. The PACH5N delivers over 2,000 CFM at 1.5" on Evaporator, 1.0" on Condenser of External Static Pressure on both the evaporator and condenser allowing longer duct runs. The PACH5N was designed with the rental/temporary industry in mind with 8" Casters for easy mobility on any job site. The Low profile design provides easy maneuverability. As with all UCA portable products, the PACH5N is rated for both indoor and outdoor applications.

PACH5N Narrow Portable Unit

Standard Features

- Air-Cooled 5 Ton
- Refrigerant R-410a
- Powder Coated Hd Steel Cabinet
- 14" Removable Duct Collars (1 Supply 1 Return)
- 8" Swivel Casters with Brakes
- Condenser Coil Guards
- Ductable Condenser Discharge
- Flooded Condenser
- Toggle Switch for 208/230
- Available Voltages: 208/230-1-60, 208/208/230-3-60, 460-3-60
- 4-Way Forklift Pod

- Stainless Steel Drain Pan with Threaded Drain Conn (Side)
- Condensate P-Trap
- SS Duct Collar Protection Bar
- Slotted Quarter-Turn Access Panel Latches
- Insulated Evaporator Section Thermal / Acoustic
- 2" Merv 8 Pleated Disposable Filters
- Single Scroll Compressor
- 10 Kw Electric Heat (Single Phase)
- 15 Kw Electric Heat (Three Phase)
- Hour Meter

- Liquid Line Filter Drier
- Liquid Receiver Tank
- Main Circuit Breaker with Cover
- Thermostat (Analog)
- Belt Drive Blowers for Static Capability
- Basic Phase / Voltage Protection
- High / Low Pressure Controls
- Remote Thermostat Capability
- Refrigerant Line Vibration Absorbers
- · Voltage Meter
- Toggle Switch for Remote Thermostat
- Camlock Power in Connection

NOTE: Includes an Optional Remote Thermostat with Cable and Condensate Pump External with Bracket

Physical Data						
	Model Number	Tons	Dimensions (W x H x L)	Approx. Weight	Voltage/Phase	MCA
Cooling/Heating	PACH5N	5	29.5 x 54.5 x 67	690	230/1 230/3 460/3	55.6 36.6 17.2

NOTES:

Products can be configured with select features and a wide variety of options than what are listed. Please contact United CoolAir to discuss special features, paint colors, capabilities and configurations. For special orders there is a minimum order of 25 units.



Scan to learn more about all of our products!







491 East Princess Street, York, PA 17403 Phone: 717-843-4311 Fax: 717-854-4462 www.unitedcoolair.com/portable-environmental-control-units/