

PROVIDING A BETTER CLIMATE ANYWHERE.







1.5 Ton Deluxe Portable Heat Pump

Product Features:

- Solid State Electronic Controller
- Automatic Mode Changeover
- Manual or Auto 6-Speed Fan Control
- Large LED Display
- Swivel Ball Bearing Casters with Locking Fronts
- Condensate Overflow Alert
- High Pressure Safety Switch
- Washable Electrostatic Air Filters

Technical Specifications:

Specifications subject to change without notice

Cooling Capacity: 16,800 BTUH
Heating Capacity: 15,000 BTUH
Voltage: 115V, 60Hz, 1PH

Amps: 14.1 Total Watts: 1670

Cooling Ambient: Operating Range

65° to 105°

Heating Ambient: Operating Range

40° to 85°

Outdoor Use: No

Cooling Capacity: Total BTUH at

80°DB/67°WB

Return Air 95°F Outdoor

at High Fan Speed.

Heating Capacity: Total BTUH at

70°DB/60°WB Indoor, 47°DB/43°WB Outdoor

In Rush Amps: 75

Net Weight:

Plug Type: 5-20P, LCDI

EER: 10.0

NOTE: Dedicated circuit and time delay fuses / circuit breakers are recommended.

Compressor: Rotary Compressor HP: 1 1/2 Compressor LRA: 63 EVAP CFM - High: 600 **EVAP Motor HP:** 1/8 COND CFM 930 COND MOTOR HP 1/8 Condensate Tank: 5 Gallon Pump Optional Refrigerant Charge: 40 oz R-410A Height: 46.7" Width: 24" 31.5" Depth:

260 lbs.






Optional Accessories



Ceiling Panel Kit
For discharging the condenser air above a drop ceiling
Part Number: CK-12



Nozzle Kit / 2 x 6"For directional cooling
Part Number: 2NK-2



Evaporator Return Air Plenum For ducting return air Part Number: 2DEP-12



Discharge Duct AdapterFor extended duct length
Part Number: 2DDA-10



Universal Condensate Pump KitFor unattended operation
Part Number: UPK-115



Condenser Return Air PlenumFor installations where it is required to duct air to the inlet of the condenser.
Part Number: 2DCP-2



OceanAire, Inc. 1731 Wall Street, Suite 100 Mount Prospect, Illinois 60056

OA-TS-2OACH1811-01.03.22

